

Christie D4K40-RGB

Giant screens
Large-scale events
Large venues
Planetariums and domes
Projection mapping
Sports venues
Theme park attractions



Pure laser. Pure performance. Pure excellence.

Take large-scale projection to new heights with the Christie® D4K40-RGB. This all-in-one, 40,000 lumen RGB pure laser projector raises the bar for design, image quality and processing. Featuring Christie RealLaser™ illumination and TruLife™ electronics, the D4K40-RGB is a powerhouse projector engineered to light up the largest canvases with spectacular visuals.

All-in-one design

What sets the Christie D4K40-RGB apart? Thanks to our engineering expertise, we designed the smallest and lightest high-brightness, large venue RGB laser projector available. There are no heavy external chillers, remote laser racks, or special pedestals - everything is completely integrated into a single chassis.

Spectacular visuals

Christie RealLaser provides an exceptionally wide color gamut and when combined with TruLife electronics and 4K resolution, allows the D4K40-RGB to reveal amazing depth of detail. Add high frame rate capabilities up to 120fps, 5000:1 On/Off contrast ratio, omnidirectional capabilities, and the D4K40-RGB sets the new standard for large-scale projection.

CHRISTIE®

Preliminary specifications		Christie D4K40-RGB
Image	brightness	• 40,000 ANSI lumens (typical) @ 25°C
	contrast	• 5000:1 On/Off (with high-contrast lens)
Display technology	type	• 3DLP® 1.38" sealed to the prism
	resolution	• 4096 x 2160 (4K)
Illumination	type	• Christie® RealLaser™ (solid state illumination)
	typical lifetime	• 20,000 hrs ¹
Orientation		• Omnidirectional
Image processing		• Christie TruLife™ electronics, 1.2Gpx/s
Frame rates		• 24-60Hz standard • Optional 96-120Hz 4K, 240-480Hz 2K scaled
Inputs	standard	• 2 x 12G-SDI1 x HDMI 2.0 • 1 x DisplayPort 1.2 (HBMIC) • 1 x Fiber (QSFP+) for use with Christie Link Transmitter • HDBaseT
	optional	• Dual 3G SD/HD-SDI input card • Dual Link DVI input card • Quad DisplayPort input card • Twin HDMI input card • Terra (SDVoE) Input Card
Lenses	available in high brightness and high contrast	• 0.72:1 • 0.9:1 • 1.13-1.66:1 • 1.45-2.17:1 • 1.95-3.26:1 • 2.71-3.89:1 • 3.89-5.43:1 (not available in the USA)
Input line voltage		• Single phase 220 VAC, 19A, 3500W, 11,942 BTU/h • Connector: 30A IEC309
Cooling		• Liquid, self-contained
Laser class		• Class 1 - Risk Group 3
Operating environment		• 5-40°C (41-104°F) • Relative humidity: 10-80% non-condensing
Dimensions	size (not including lens)	• (LxWxH): 37 x 28 x 21.8" (947 x 711 x 553mm)
	weight	• 285lbs (130kg)

¹to 60% brightness

Key features:

- › **All-in-one, compact design** - No external chillers, laser racks or parts, and a manageable weight of 285 lbs makes it the smallest and lightest high-brightness laser projector available
- › **Omnidirectional** - Operates in any orientation for increased installation flexibility
- › **Long-lasting, reliable light source** - Typical lifetime of 20,000 hours¹
- › **High contrast** - Achieves 5,000:1 On/Off contrast for amazing depth of detail
- › **Expanded color gamut** - Produces >90% of the Rec. 2020 color space for rich, vibrant and true-to-life visuals
- › **Energy efficient** - Consumes less power than any other 40,000 lumen RGB laser projector with 220V single phase operation
- › **Christie Terra input card** - Seamlessly integrates into SDVoE networks
- › **Boxer lens compatibility** - Compatible with most Christie Boxer lenses

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610
Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888
Brazil
ph: +55 (11) 2548 4753
China (Beijing)
ph: +86 10 6561 0240
China (Shanghai)
ph: +86 21 6030 0500
Colombia
ph: +57 (318) 447 3179
Eastern Europe
ph: +36 (0)1 47 48 138

France
ph: +33 (0) 1 41 21 44 04
Germany (Cologne)
ph: +49 221 99 512-0
Germany (Mönchengladbach)
ph: +49 2161 566200
India
ph: +91 (080) 6708 9999
Japan
ph: +81 3 3599 7481
Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000
Singapore
ph: +65 6877 8737
South Korea
ph: +82 2 702 1601
Spain
ph: +34 91 633 9990
United Arab Emirates
ph: +971 (0) 4 503 6800
United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700
United States (New York)
ph: 646 779 2014

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161
Russia
ph: +7 (495) 930 8961



For the most current specification information, please visit www.christiedigital.com

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4736 Nov 18

CHRISTIE®